



MATERIAL SAFETY DATA SHEET

LPS[®] PF[®]-400

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 1 • Product and Company Identification

Product Name: LPS[®] PF[®]-400

Part Number: 62716, C62716

Chemical Name: Isoparaffinic Hydrocarbon

Product Use: An industrial grade solvent designed to remove contaminant particles from high voltage cables.

Manufacturer Information: LPS Laboratories, 4647 Hugh Howell Rd., Tucker, GA, USA 30084

TEL: 1 770-243-8800

Emergency Telephone Number: 1-800-424-9300 Chemtrec;
Outside U.S.: (703) 527-3887

FAX: 1 770-243-8899

Website: <http://www.lpslabs.com>

PLAIN LANGUAGE HAZARD SUMMARY

Material Safety Data Sheets can be confusing. Federal and State laws require us to include a great deal of technical information that probably won't help the non-professional. LPS includes this "PLAIN LANGUAGE HAZARD SUMMARY" to address the questions and concerns of the average worker. If you have additional health, safety or product questions, don't hesitate to call us at 800/241-8334.

Worker Toxicity

An industrial grade spray solvent designed to remove contaminant particles from high voltage cables. It contains isoparaffinic hydrocarbons that can be irritating to skin. We suggest you wear gloves and avoid extended exposure to unprotected skin. Don't get it in your eyes (it stings), or breath large amounts of the vapor, (it will dry out your nasal passages and if you breathe large amounts in poorly ventilated areas it can make you dizzy and even sick). Don't use LPS[®] PF[®]-400 for extended periods without adequate ventilation. If you're going to perform work involving a lot of product in a poorly ventilated area, use of a respirator or even a self-contained breathing apparatus may be necessary. For more exposure and first aid information, refer to MSDS Sections 2, 8 and 11.

Flammability

LPS[®] PF[®]-400 is a flammable aerosol. Do not use on red-hot metal surfaces. Store product away from heat sources and do not use on live electrical equipment.

Disposal

If you spill LPS[®] PF[®]-400, notify the proper environmental or safety department at your company right away. If LPS[®] PF[®]-400 becomes contaminated with another substance and is rendered unusable for cleaning, the resulting mixture may fall under at least one hazardous classification. See section 13.



MATERIAL SAFETY DATA SHEET

LPS[®] PF[®]-400

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 2 • Hazards Identification

*This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.*

Emergency Overview:

Aerosol: DANGER: Flammable. Contents under Pressure. Harmful or fatal if swallowed.

Primary route(s) of entry: Skin and Eye contact. Inhalation.

Potential Acute Health Effects:

Eyes Irritating to eyes

Skin Repeated exposure may cause skin dryness or cracking.

Inhalation: Excessive inhalation of vapors can cause irritation of the respiratory tract, nausea, dizziness or headache.

Ingestion: Product has a low order of acute oral toxicity, but ingestion of large quantities may cause nausea, vomiting, and gastrointestinal irritation. May cause injury if aspirated into lungs.

Potential Chronic Health Effects:

Carcinogenic Effects: NTP: No IARC: No OSHA: No

Mutagenic Effects: None

Teratogenic Effects: None

Medical conditions aggravated by exposure: Persons with pre-existing central nervous system (CNS) disease, neurological conditions, skin disorders, chronic respiratory diseases, or impaired liver or kidney function should avoid exposure.

Signs and Symptoms

Stinging in eyes. Repeated or prolonged skin contact can cause redness, irritation, and scaling of the skin (dermatitis). Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes, and kidney effects.

Section 3 • Composition / Information on Ingredients

Component	CASRN	Percent by Weight
Aliphatic Hydrocarbon	64742-48-9	80 - 100%
Carbon Dioxide	124-38-9	2 - 4%



MATERIAL SAFETY DATA SHEET

LPS[®] PF[®]-400

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 4 • First Aid Measures

- Eyes:** Check for and remove contact lenses. If irritation or redness develops, flush eyes with cool, clean, low pressure water for at least 15 minutes. Hold eyelids apart to ensure complete irrigation of the eye and eyelid tissue. Do not use eye ointment. Seek medical attention immediately.
- Skin:** Remove contaminated shoes and clothing. Clean affected area thoroughly with mild soap and water. Do not use ointments. Seek medical attention if irritation persists.
- Inhalation:** Immediately move victim to fresh air. If victim is not breathing, immediately begin rescue breathing. If heart has stopped, immediately begin cardiopulmonary resuscitation (CPR). If breathing is difficult, seek medical attention immediately.
- Ingestion:** Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. If spontaneous vomiting is about to occur, place victim's head below knees. If victim is drowsy or unconscious, place on the left side with head down. Do not leave victim unattended. Seek medical attention immediately.

Section 5 • Fire Fighting Measures

Products of Combustion: Carbon monoxide and carbon dioxide. **NFPA Class:** IIIA Liquid

Firefighting media: SMALL FIRE: Use DRY chemical powder.
LARGE FIRE: Use water spray, fog or foam. Cool containing vessels with water jet in order to prevent pressure build-up, autoignition or explosions.

Sensitivity to Impact: None. **Sensitivity to Static Discharge:** None.

Protection Clothing (Fire): Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.

Special Remarks on Explosion Hazards: High heat will cause product to boil, evolving vapor that could cause explosive rupture of closed containers. Aerosols may explode upon heating, spread fire and overcome sprinkler systems.

Section 6 • Accidental Release Measures

- Containment Procedures** Contain and recover spilled liquid when possible.
- Clean-Up Procedures**
- Small Spill and Leak:** Absorb with an inert material and dispose of properly.
- Large Spill and Leak:** Secure the area and control access. Dike far ahead of a liquid spill to ensure complete collection. Pick up free liquid for disposal using absorbent pads, sand, or other inert non-combustible absorbent materials. Place into appropriate waste containers for later disposal.
- Evacuation Procedures** Ventilate area of leak or spill. Keep unnecessary and unprotected people away.
- Special Procedures** Remove all sources of ignition. Ventilate area. Wear appropriate protective equipment during cleanup.



MATERIAL SAFETY DATA SHEET

LPS[®] PF[®]-400

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 7 • Handling and Storage

Handling: DO NOT spray into or around ignition sources. Do not allow material to come into contact with eyes or skin. Wear appropriate protective equipment during handling. Keep container closed. Do not breathe vapors or mists. Use only with adequate ventilation. Wash thoroughly after handling.

Storage: Keep container in a cool, well-ventilated area. Avoid all sources of ignition (spark or flame). Store below 120°F.

Precautions to be taken in handling and storage: Store aerosols as Level 3 Aerosol (NFPA 30B). Store all materials in dry, well-ventilated area. Avoid breathing vapors.

Section 8 • Exposure Controls / Personal Protection

Exposure Guidelines:

Component	CASRN	OSHA TWA-PEL	OSHA STEL	ACGIH-TLV	ACGIH-STEL	NIOSH REL
Aliphatic Hydrocarbon	64742-48-9	171 ppm*	Not Established	Not Established	Not Established	Not Established
Carbon Dioxide	124-38-9	5,000 ppm	Not Established	5,000 ppm	30,000 ppm	5000ppm 3000 ppm STEL

* Supplier Recommendation

Engineering measures Provide general and/or local exhaust ventilation to keep exposures below the exposure guidelines listed above.

Personal protective equipment

Eye protection Safety glasses with side shields conforming to appropriate regulations. Eye wash fountain and emergency shower facilities are recommended.

Hand protection Normally no hand protection is required; however, if product will be sprayed for an extended period, "overspray" onto skin may occur. If so, use chemical resistant gloves (i.e., nitrile) conforming to appropriate regulations. Please observe the instructions regarding permeability and breakthrough time that are provided by the supplier of the gloves.

Respiratory protection Typical use of this product under normal conditions does not require the use of respiratory protection. If airborne concentrations are above the applicable exposure limits (listed above), use NIOSH approved respiratory protection (i.e., organic vapor cartridge).

General Hygiene Considerations Wash thoroughly after handling. Have eye-wash facilities immediately available.



MATERIAL SAFETY DATA SHEET

LPS[®] PF[®]-400

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 9 • Physical and Chemical Properties

Appearance:	Liquid.	Color:	Clear/Colorless
Odor/Taste:	No Odor	Vapor Pressure:	0.49mmHg (0.064kPa) at 20°C
Solubility Description:	Insoluble in cold water	Evaporation Rate:	0.1 (BuAc=1)
Boiling Point:	185°C(365 °F) -211°C(412°F) @ 760mmHg	Flash Point:	>61°C (142°F)
Specific Gravity (Water=1):	0.74-0.78 @ 20 °C	Flash Point Method:	Tag-Closed Cup.
Vapor Density (air=1):	5.6 at 101kPa	Auto Ignition Temperature (°C):	Not Established
V.O.C. Content:	97%, 749 g/L, 6.26#/gal. Per C.A.R.B / O.T.C. and S.C.A.Q.M.D. Rule 102	Partition Coefficient (octanol/water):	Not Established
Flammable limits (estimated):	LOWER: 0.7% UPPER: 5.3%	Volatiles:	100%
Viscosity:	1.99 cSt at 25°C	Auto Ignition Temperature (°C):	>260°C (500°F)
pH:	Not applicable		

Section 10 • Stability and Reactivity

Chemical Stability:	Product is stable under recommended storage conditions.
Conditions to Avoid:	Keep away from heat and ignition sources.
Incompatibility:	Reactive or incompatible with oxidizing agents.
Hazardous Decomposition:	These products are carbon oxides (CO, CO2)
Hazardous Polymerization:	Will not occur.

Section 11 • Toxicological Information

A: General Product Information

An acute toxicity study of this product has not been conducted. Information given in this section relates only to individual constituents contained in this preparation.



MATERIAL SAFETY DATA SHEET

LPS PF 141IG Industrial Grade Solvent

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

B: Component Analysis

Component	CASRN	LC-50	LD-50
Aliphatic Hydrocarbon	64742-48-9	Not established	>10000 mg/kg oral* >3160 mg/kg dermal*
Carbon Dioxide	124-38-9	Not Available	Not Appropriate

* Supplier data

Section 12 • Ecological Information

Mobility: Volatile. Not expected to partition to sediment. **Persistence and degradability:** Readily biodegradable

Bioaccumulative potential: No bioaccumulation potential **Other adverse effects:** None known.

Ecotoxicology:

Effect on Organisms	Component	CASRN	Test	Species	Results
Acute Toxicity on Fishes					No Data Available
Acute Toxicity on Daphnia					
Bacterial inhibition					
Growth inhibition of algae					
Bioaccumulation in fish					

Section 13 • Disposal Considerations

Waste Status: Aerosol products, if depressurized and emptied to less than 2.5 cm of fluid contents are classified as non-hazardous waste under 40 CFR 261.7 (U.S.). This product, if disposed of in its received form carries waste codes D003 (aerosol only) (U.S.).

Disposal: Waste must be disposed of in accordance with federal, state, provincial, and local environmental control regulations.

Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information inaccurate, incomplete, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive than federal laws and regulations.



MATERIAL SAFETY DATA SHEET

LPS PF 141IG Industrial Grade Solvent

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

Section 14 • Transport Information

D.O.T. Ground	Shipping Name:	Consumer Quantity	UN Number:	NA
	Hazard Class:	ORM-D	Technical Name:	NA
	Subclass:	NA	Hazard Label:	ORM-D Already on box
Road/Rail - ADR/RID	UN no:	1950	ADR Class:	2
	Packing group:	NA	Classification code:	5F
	Name and Description:	AEROSOLS, Flammable	Hazard ID no:	NA
	Labeling:	2.1		
IMDG-IMO	UN no:	1950	Class:	2.1
	Shipping Name:	AEROSOLS	Subsidiary Risk:	2.1
	Packing Instructions:	P003, LP02	Packing group:	NA
	Marine pollutant:	NO	EmS:	F-D, S-U
IATA-ICAO	UN no:	1950	Class:	2.1
	Shipping Name:	AEROSOLS, Flammable	Subclass	NA
	Packing instructions:	203, Y203 (Ltd. Qty.)	Packing group:	NA
	Labeling:	Flammable Gas		

Section 15 • Regulatory information

U.S. Federal Regulations

RCRA Hazardous Waste No.: D003 (aerosol)

Comprehensive Environmental Response and Liability Act of 1980 (CERCLA): None

Toxic Substances Control Act (TSCA):

All components of this product are TSCA inventory listed and/or are exempt.

Superfund Amendments and Reauthorization Act (SARA) Title III

SARA Section 311/312 (40 CFR 370) Hazard Categories:

Sudden Release of Pressure (aerosols only), Fire Hazard, Immediate (Acute) Health Hazard, Delayed (Chronic) Health Hazard

This product contains the following toxic chemical(s) subject to reporting requirements of SARA Section 313 (40 CFR 372): No individual section 313 component is present at or above 1%

Section 112 Hazardous Air Pollutants (HAPs): None



MATERIAL SAFETY DATA SHEET

LPS PF 141IG Industrial Grade Solvent

Revision: 4

Revision Date: 11/25/08

Supersedes: 7/10/08

State Regulations

New Jersey RTK: Aliphatic Hydrocarbon 64742-48-9 • Carbon Dioxide 124-38-9

California: This product does not contain chemical(s) known to the State of California to cause cancer, birth defects or reproductive harm.

International Regulations

Canadian Environmental Protection Act: All of the components of this product are included on the Canadian Domestic Substances list (DSL).

Canadian Workplace Hazardous Materials Information System (WHMIS):

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations.

WHMIS Classification:

Class B3, Class D2B

**Other Regulations**

Montreal Protocol listed ingredients: None.
 Stockholm Convention listed ingredients: None.
 Rotterdam Convention listed ingredients: None.
 RoHS Compliant: Yes.

Section 16 • Other Information

MSDS# 162716 Responsible Name: Clea Johnson Regulatory Affairs Coordinator	HMIS 1996		HMIS III		NFPA	
	Health:	1	Health:	[1]	Flammability Health Reactivity	
	Flammability:	2	Flammability:	2		
	Reactivity	0	Physical Hazard:	2		

Notice to Reader:

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

Clea Johnson, Regulatory Affairs Coordinator
 LPS Laboratories, A division of Illinois Tool Works