



# DRY FILM PTFE LUBRICANT



Qualified to: Learjet M3735-01-98-0042

## FEATURES

- Provides excellent lubrication
- Ideal for releasing molded parts
- Excellent for high temperature applications up to 500°F (260°C)
- Dry, thin film will not attract dust or dirt
- Non-flammable
- Does not contain silicone or chlorinated solvents
- Safe on most surfaces

## PACKAGE

Net Fill

12 oz. (340 grams) aerosol

Part No.

02616

## APPLICATIONS

- Chutes & Slides
- Conveyor Belts
- Injection Molding
- Locks & Catches
- Metal Extrusions
- Silicone Rubber
- Tanks & Bins
- Thermoplastics
- Thermosets
- Window Guides



## PROPERTIES

Appearance/Physical State:

White (when dry)

Evaporation Rate:

>1 (Butyl Acetate=1)

HMIS:

1, 3, 0

Specific Gravity (water=1):

0.64 – 0.66 @ 20°C

Vapor Pressure:

630 kPa (25°C)

Viscosity:

<2 centistokes @ 25°C

VOC Content:

57%

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :[WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)

©2009 LPS Laboratories • LPS®, PT® and PF® are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2163 • Rev. 6/2009