

# LPS® **ELECTRO 140°**



Conforms to:

Bombardier (Canadair) CMS 570-01  
Learjet LES 1239  
McDonnell Douglas CSD #1

## FEATURES

- Flash point above 140°F (60°C)
- Superior wetting and penetrating action
- Controlled evaporation
- No residue
- Non-conductive
- Safe to use on most surfaces
- Ideal for parts washer, dip tanks and ultrasonic cleaning tank
- Inverta Spray Valve

## PACKAGES

### Net Fill

11 oz. (312 grams) aerosol  
1 gal. (3.78 liters)  
5 gal. (18.93 liters)  
55 gal. (208 liters)  
20 fl.oz (591 ml) trigger spray

### Part No.

00916  
09128  
00905  
00955  
00922

## APPLICATIONS

- Coin Counters & Chutes
- Relays and Controls
- Connectors
- Semiconductor Assemblies
- Contacts
- Switches
- Fluid Systems
- Telephone Equipment
- Office Equipment
- Printed Circuits

## PROPERTIES

### Appearance/Physical State:

Clear liquid

### Dielectric Strength (ASTM D-877):

15.14 kV

### Flash Point (TCC):

144°F (62°C)

### HMIS:

1, 2, 0

### Surface Tension:

25.9 dynes/cm @ 77°F (25°C)

### Propellant:

CO<sub>2</sub>

### Specific Gravity:

0.79



MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE: [WWW.LPSLABS.COM](http://WWW.LPSLABS.COM)

**LPS Laboratories** • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

**Internet Web Site: [www.lpslabs.com](http://www.lpslabs.com)**

©2009 LPS Laboratories • LPS® is a registered trademark of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2086 • Rev. 3/2009