



FOOD GRADE SILICONE LUBRICANT



FEATURES

- NSF[®] registered H1# 113815
- Meets FDA Regulation 21 CFR 178.3570 for Incidental Food Contact
- Provides excellent lubrication
- Great for food processing and food handling applications
- Ideal for releasing molded parts
- Dry film won't attract dust or dirt
- Excellent for high temperature applications up to 500°F
- Does not contain chlorinated solvents
- Canadian Food Inspection Agency (CFIA) approved



Nonfood Compounds Program Listed
Category Code: H1 Registration
113815

PACKAGE

Net Fill

10 oz. (284 grams) aerosol

Part No.

01716



APPLICATIONS

- Blow Molders
- Bottling Machines
- Chutes
- Compression Molders
- Conveyors
- Food Racks
- Injection Molders
- Plastic Gears
- Rubber Mountings
- Slides

PROPERTIES

Appearance/Physical State:

Clear/ colorless liquid

Auto Ignition Temperature

583°F (306°C)

Evaporation Rate:

<1 (Ethyl Ether=1)

HMIS:

1, 3, 0

Propellant:

Propane/Isobutane blend

Specific Gravity (water=1):

0.64 – 0.66 @ 20°C

Vapor Pressure:

352 mmHg @ 38°C

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE :WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2009 LPS Laboratories • LPS[®], PT[®] and PF[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2161 • Rev. 9/2009