



TAPMATIC[®] CUTTING FLUID

NATURAL



FEATURES

- Biodegradable
- Non-toxic & non-hazardous
- Natural-based oils
- Great for cutting steel & aluminum
- Extends tool life
- Does not contain sulfur, chlorine, chlorinated solvents, water, mineral oil, or inactive fillers
- High performance lubricating ability eliminates galling & seizing
- Safe on all metals

PACKAGE

Net Fill

- 16 fl.oz. (0.473 liter) bottle
- 1 gal. (3.78 liters) container
- 5 gal. (18.93 liters) pail
- 55 gal. (208 liters) drum

Part No.

- 44220
- 44230
- 44240
- 44260

APPLICATIONS

- Boring
- Broaching
- Drilling
- Engraving
- Facing
- Milling
- Reaming
- Sawing
- Tapping
- Threading
- Turning



PROPERTIES

Appearance:

Clear, green liquid

Odor:

Citrus spice

Flash Point:

350°F (176°C) C.O.C.

Specific Gravity (H2O = 1):

0.88 – 0.89 @ 68°F (20 °C)

NFPA:

1,1,0

HMIS:

1,0,0

V.O.C.:

0%, 0 g/L, 0 lbs./gal.

MATERIAL SAFETY DATA SHEETS AVAILABLE UPON REQUEST OR VISIT OUR WEB SITE : WWW.LPSLABS.COM

LPS Laboratories • An Illinois Tool Works Company

P.O. Box 105052 • 4647 Hugh Howell Road • Tucker, GA 30085-5052 • TEL: (800) 241-8334 or (770) 243-8800 • FAX: (800) 543-1563 or (770) 243-8899

Internet Web Site: www.lpslabs.com

©2008 LPS Laboratories • LPS[®] and Tapmatic[®] are registered trademarks of Illinois Tool Works • Printed in U.S.A. • All Rights Reserved • Form #2076 • Rev. 7/2008